newline

















SIMPLICITY MADE FOR EVERY USER

A 4K interactive display that is ready when you are. Just connect your device to start, no setup, no hassle, and no learning curve. With paper-like writing, 40 touch points, built-in speakers, and Plug and Play USB Type-C connectivity, it is a complete solution. Designed to be easy and effective, the Newline C Series keeps you focused on teaching or teamwork, not on technology.



BULT-IN COMPUTER INTERGRATION

Complete your display with an embedded OPS PC, bringing Windows directly to your display for a seamless all in one experience. Turn it on and get started!






65 W Powered USB Type-C



Broad Compatibility



4K HD Resolution



With **Plug and Play**, just connect one USB-C cable for instant audio, video, power, data, and touch. No delays, just start working.







High Quality Sound System



Diverse Connectivity













86"

MODEL



| MODEL | |
|-----------------------------|--|
| C Series 65" | TT-6523C |
| C Series 75" | TT-7523C |
| C Series 86" | TT-8623C |
| | |
| PANEL | |
| Backlight | Direct LED (Wide Color Gamut + Anti Blue Light) |
| Glass Surface | Anti-Glare + Anti-Fingerprint + Antimicrobial Tempered Glass |
| Bonding Technlogy | Certified Zero Bonding |
| Display Area | 65": 1429 x 804 mm 75": 1651 x 929 mm 86": 1896 x 1066 mm |
| Display Ratio | 16:9 |
| Resolution | 3840 x 2160 (4K) |
| Colours | 1,07 Billion |
| Brightness | 55": 450 cd/m² 65": 450 cd/m² 75": 450 cd/m² 86": 450 cd/m² 98": 450 cd/m² |
| Contrast Ratio | 4000:1 |
| Response Time | 5 ms |
| Viewing Angle | 178° |
| Display Life Time | ≥ 50 000 hours |
| Transparency | > 88% |
| Haze | 2 % ~ 5 % |
| Touch Surface Hardness | 7 MoHs, Pencil 9H |
| POWER CONSUMPTION | |
| Standard Mode* | 65": 91 W 75": 116 W 86": 146 W |
| Standby mode* | <0,5 W |
| TOUGH | |
| TOUCH Touch Technology | Stellar Touch Technology |
| | 40 Windows |
| Touch Points | 20 Android/MAC/Linux |
| Touch Screen Writing Tools | Passive pen, Finger, Fist |
| Number of stylus | 2 |
| Accuracy | ±1 mm |
| | |
| SPEAKER | |
| Speaker Position | Front Facing |
| Speaker Rated Impedance | 6 Ω |
| Speaker Max.Power Output | 15 W x 2 |
| FRONT I/O | |
| USB Type-C (Powered 65 W) | 1 |
| HDMI IN 2.0 (4k @60 Hz) | 1 |
| USB 2.0 Type-B (Touch) | 1 |
| USB 3.0 Type-A (Dynamic) | 2 |
| Microphone In (Jack 3,5 mm) | 1 |
| | |

| REAR I/O | |
|------------------------------|------------------|
| HDMI IN 2.0 (4k @60 Hz) | 2 |
| USB 2.0 Type-B (Touch) | 1 |
| USB Type-A 2.0 (Dynamic) | 2 |
| USB Type-A 2.0 (Embedded) | 1 |
| RS232 | 1 |
| RJ45 (Gigabit) | In x 1 / Out x 1 |
| OPS Slot | 1 |
| SPDIF | 1 |
| Audio Line Out (Jack 3,5 mm) | 1 |
| VGA In | 1 |
| USB Type-C (Camera Slot) | 1 |
| | |

| SMAK | 15 | Y S I | EN |
|------|----|-------|----|
| | | | |

| SoC Chipset | Arm Cortex-A55 x 4 |
|--------------------------------|--------------------|
| RAM | 2 GB |
| Total Storage | 8 GB |
| Operating System | No OS |
| Wi-Fi 6 + Bluetooth 5.2 Module | Integrated |

DIMENSIONS / WEIGHT

| Outline Dimensions* (Excl. wall mount) | 65": 1513 x 923 x 110 mm 75": 1735 x 1048 x 111 mm 86": 1981 x 1186 x 111 mm |
|---|--|
| Net Weight* | 65": 38,5 Kg 75": 50 Kg 86": 74 Kg |
| VESA* | 65": 600 x 400 mm 75": 800 x 400 mm 86": 800 x 400 mm |

The provided measures are indicative and subject to further adjustments. They are not yet considered definitive.



Newline-interactive.com/eu
Contact us at: Info_eu@newline-interactive.com / Support_eu@newline-interactive.com / Technical Support Hotline: +34 91 804 31 79

2025 Newline Interactive Europe S.L. All Rights Reserved, Newline logo is a registered trademark in the United States and other countries around the world. Product specifications may vary by region, please contact our local offices for details. All weights and dimensions are approximate. Actual product features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.







